

WHAT IS CLAIMED IS:

1. A clock regeneration circuit, comprising:

5 a PLL circuit which includes a voltage control oscillator,
for synchronizing an oscillation frequency signal of the
voltage control oscillator with a phase of a reception signal;

10 a clock extraction circuit which includes a band passing
filter having a passing band width which concurrently extracts
a basic waves component of the oscillation frequency signal of
the voltage control oscillator and a harmonic component of a
dividing signal of the oscillation frequency signal, for
extracting a clock component of the reception signal;

15 a frequency detector for detecting a different in
frequencies between an output of the clock extraction circuit
and an oscillation frequency of the voltage control oscillator;

a filter for controlling the oscillation frequency of the
voltage control oscillator of the PLL circuit at a detection
output of the frequency detector;

20 a bit rate detection circuit for detecting a bit rate of
the reception signal; and

25 a frequency selection circuit for outputting an
oscillation frequency of the voltage control oscillator of the
PLL circuit or a frequency signal obtained by dividing the
oscillation frequency in response to the bit rate detected by
the bit rate detection circuit, as a regeneration clock signal.

2. The clock regeneration circuit according to claim 1,

wherein

the clock extraction circuit further includes:

a delay circuit for delaying the reception signal by the half cycle; and

5 an EX-OR circuit for acquiring an exclusive OR operation of an output of the delay circuit and the reception signal, wherein

the output of the EX-OR circuit is led to the band passing filter in the configuration.

10

3. The clock regeneration circuit according to claim 1, wherein

the bit rate detection circuit includes:

15

a first AND gate for taking a conjunction of the reception signal and the oscillation frequency signal of the voltage control oscillator of the PLL circuit;

a delay circuit for delaying an output of the first AND gate by 1 cycle of the oscillation frequency signal of the voltage control oscillator;

20

a second AND gate for taking a conjunction of an output of the first AND gate and an output of the delay circuit; and

a circuit for acquiring an average value of the output of the AND gate.

25

4. The clock regeneration circuit according to claim 1, wherein

the bit rate detection circuit includes:

an AND gate for synthesizing the reception signal with
a signal obtained by inverting the reception signal; and
a circuit for acquiring an average value of the output
of the AND gate.

5

5. The clock regeneration circuit according to claim 1,
wherein

the bit rate detection circuit includes:

an AND gate for synthesizing the reception signal with
a signal obtained by inverting the reception signal; and
a circuit for counting a change point of the output of
the AND gate.

10

6. An optical signal receiver, comprising:

a light receiving element for converting a received light
signal into a reception electric signal;

a PLL circuit which includes a voltage control oscillator,
for synchronizing an oscillation frequency signal of the
voltage control oscillator with a phase of a reception electric
signal;

20

a clock extraction circuit which includes a band passing
filter having a passing band width which concurrently extracts
a basic waves component of the oscillation frequency signal of
the voltage control oscillator and a harmonic component of a
dividing signal of the oscillation frequency signal, for
extracting a clock component of the reception signal;

25

a frequency detector for detecting a difference in

frequencies between an output of the clock extraction circuit and an oscillation frequency of the voltage control oscillator;

a loop filter for controlling the oscillation frequency of the voltage control oscillator of the PLL circuit by a
5 detection output of the frequency detector;

a discriminator for discriminating a level of the reception electric signal at a frequency timing of the output of the PLL circuit to output discrimination data;

a bit rate detection circuit for detecting a bit rate of the reception signal; and
10

a frequency selection circuit for outputting an oscillation frequency of the voltage control oscillator of the PLL circuit or a frequency signal obtained by dividing the oscillation frequency in response to the bit rate detected by the bit rate detection circuit, as a regeneration clock signal.
15

Add A27